

DLC6240

TFT LCD Color Monitors

NTSC/PAL 7", 8.5"



DESCRIPTION

The DLC6240 Series are high resolution, 7" and 8.5" TFT Color Monitors compatible with NTSC and PAL composite video, signals. Units feature Four (4) Video inputs and Remote Control for Channel select. Set-up and adjustment of parameters via controls are conveniently located on the front panel. Available with 12VDC input voltages, the DLC6240 Series provide quality, high resolution images and are a perfect solution for Mobile based video surveillance installations.



FEATURES

- * NTSC/PAL TFT LCD Color Monitors
- * 7" - 4 Video; 8.5" - 4 Video, 1 Audio
- * 1440 x 234 Resolution
- * Display Format 16:9
- * Blue Screen on Video loss
- * Front Panel controls with OSD Functions
- * Channel Select via Remote Control
- * Slim Lightweight, Space Saving Design
- * Vehicle Mounting Bracket
- * Regulatory Compliance with CE, FCC

APPLICATIONS

- * Police Vehicles
- * Public Buses
- * Fire Dept. Trucks
- * Railways/Subways
- * Commercial Trucks
- * School Buses
- * Utility Vehicles
- * Taxi/Fleet Vehicles
- * Correctional Vehicles
- * Emergency Response

ORDERING INFORMATION

DLC6240A-1 NTSC/PAL, TFT LCD Color Monitor 7", 4 Video, 12VDC

DLC6240B-1 NTSC/PAL, TFT LCD Color Monitor 8.5" 4 Video, 1 Audio, 12VDC

General Parameters

Monitor 7": 4 Video
 Monitor 8.5": 4 Video, 1 Audio

Electrical Parameters

Input Voltage: 12VDC
 Power Consumption: 8W
 Resolution: 1440 x 234
 Contrast Ratio: 300:1
 Angle of View : 40*60*60
 Brightness: 350cd/m²
 Response Time: 15ms

Environmental Parameters

Operating Temperature: 0°C~50°C
 Operating Humidity: 5-95% noncondens.

Mechanical Parameters

Monitor 7" (no frame): 18x12x1.8cm
 Monitor 7" (w/frame): 20.6x14.6x1.8cm
 Monitor 8.5" (no frame): 22x14.6x2.5cm
 Monitor 8.5" (with frame): 24x16.6x2.6cm
 Monitor weight 7": 0.9Kg/pc
 Monitor weight 8.5": 1.1Kg/pc

Regulatory Compliance

CE, FCC
 Manufactured to: ISO9001:2000

