

# DLV6230E LED Color Monitors 22", 32", 43", 49", 55"



## DESCRIPTION

The DLV6230E Series are high resolution, 22", 32", 43", 49" and 55" LED backlit Color Monitors compatible with NTSC/PAL Composite video, VGA, HDMI and YPbPr signals. Units feature 1920 x 1080 resolutions - 1080p. Additionally, all versions provide on screen (OSD) set-up and adjustment of parameters via controls conveniently located on the front panel. Available with 100-240VAC input voltages, the DLV6230E Series provide quality, high resolution images and are serious solution for commercial and industrial legacy or IP based video surveillance installations.



## FEATURES

- \* NTSC/PAL/VGA/HDMI LED Color Monitors
- \* 1920 x 1080 Resolution - 1080p
- \* 2 BNC Video In/1 Out, VGA, HDMI, YPbPr
- \* 178°(H) and 178°(V) viewing angle
- \* On Screen Display OSD function
- \* Slim Lightweight, Space Saving Design
- \* Metal Cabinets, 22", 32", 43", 49", 55"
- \* Regulatory Compliance with CE, FCC, ROHS

## APPLICATIONS

- \* Homeland Security
- \* Correctional Centers
- \* Petrochemical Industry
- \* Corporate and Banking
- \* Casinos and Hospitality
- \* Health Care Centers
- \* Schools and Universities
- \* Government and Military
- \* Power Generating Plants
- \* Traffic Surveillance (ITS)

## ORDERING INFORMATION

DLV6230E-22-5	NTSC/PAL, LED Color Monitor, 22", 1080p, HDMI, 100-240VAC
DLV6230E-32-5	NTSC/PAL, LED Color Monitor, 32", 1080p, HDMI, 100-240VAC
DLV6230E-43-5	NTSC/PAL, LED Color Monitor, 43", 1080p, HDMI, 100-240VAC
DLV6230E-49-5	NTSC/PAL, LED Color Monitor, 49", 1080p, HDMI, 100-240VAC
DLV6230E-55-5	NTSC/PAL, LED Color Monitor, 55", 1080p, HDMI, 100-240VAC

## Electrical Parameters

Input Voltage:	100-240VAC auto range
Power Consumption:	22"- 45W; 32"- 85W 43" - 100W; 49" - 110W 55" - 120W

Resolution (all):	1920x1080 (1080p)
Angle of View (all):	178° (H), 178° (V)
Contrast Ratio 22"/32"):	2000:1 / 3000:1
Contrast Ratio (others):	4000:1
Brightness 22":	350cd/m <sup>2</sup>
Brightness (others):	500cd/m <sup>2</sup>
Response Time (all):	6ms

## General Parameters

Composite Video:	2 BNC input; 1 Output
VGA:	15 pin mini Sub D
HDMI:	22", 32", 43", 49", 55"
YPbPr:	32", 43", 49", 55"

## Environmental Parameters

Operating Temperature:	0°C~50°C
Operating Humidity:	5-95% noncondens.

## Mechanical Parameters

Dimensions W x H x D:	
22":	19.8"(502mm), 11.7"(298mm), 1.8"(46mm)
32":	29"(739mm), 17.8"(451mm), 3.7"(93mm)
43":	39"(996mm), 23.5"(596mm), 4.2"(107mm)
49":	44"(1110mm), 26"(660mm), 3.9"(100mm)
55":	50"(1269mm), 29.5"(749mm), 5.4"(137mm)
Weight 22":	13.5 lb (6Kg)
Weight 32":	27 lb (12Kg)
Weight 43":	54 lb (24Kg)
Weight 49":	72 lb (32Kg)
Weight 55":	78 lb (35Kg)

## Regulatory Compliance:

CE, FCC, ROHS

## Manufactured to:

ISO9001:2000

