

DLV6340E

LED Color Monitors

43", 49", 55", 65"
4K



DESCRIPTION

The DLV6340E Series are 4K high resolution 43", 49", 55" and 65" LED backlit Color Monitors compatible with NTSC/PAL Composite video, VGA, HDMI and YPbPr signals. Units feature 3840 x 2160 resolutions - 1080p. Additionally, all versions provide on screen (OSD) set-up and adjustment of parameters via controls conveniently located on the front panel. Available with 100-240VAC input voltages, the DLV6340E Series provide quality, high resolution images and are serious solution for commercial and industrial legacy or IP based video surveillance installations.



FEATURES

- * NTSC/PAL/VGA/HDMI LED Color Monitors
- * 3840 x 2160 Resolution - 4K
- * 2 BNC Video In/1 Out, VGA, HDMI, YPbPr
- * 178°(H) and 178°(V) viewing angle
- * On Screen Display OSD function
- * Slim Lightweight, Space Saving Design
- * Metal Cabinets, 43", 49", 55", 65"
- * Regulatory Compliance with CE, FCC, ROHS

APPLICATIONS

- * Homeland Security
- * Correctional Centers
- * Petrochemical Industry
- * Corporate and Banking
- * Casinos and Hospitality
- * Health Care Centers
- * Schools and Universities
- * Government and Military
- * Power Generating Plants
- * Traffic Surveillance (ITS)



ORDERING INFORMATION

DLV6340E-43-5	NTSC/PAL, LED Color Monitor, 43", 3840x2160, HDMI, 100-240VAC
DLV6340E-49-5	NTSC/PAL, LED Color Monitor, 49", 3840x2160, HDMI, 100-240VAC
DLV6340E-55-5	NTSC/PAL, LED Color Monitor, 55", 3840x2160, HDMI, 100-240VAC
DLV6340E-65-5	NTSC/PAL, LED Color Monitor, 55", 3840x2160, HDMI, 100-240VAC

Electrical Parameters

Input Voltage:	100-240VAC auto range
Power Consumption:	43" - 100W; 49" - 110W 55" - 120W; 65" - 140W
Resolution (all):	1920x1080 (1080p)
Angle of View (all):	178° (H), 178° (V)
Contrast Ratio (all):	4000:1
Brightness (all):	500cd/m ²
Response Time (all):	6ms

General Parameters

Composite Video:	2 BNC input; 1 Output
VGA:	15 pin mini Sub D
HDMI:	43", 49", 55", 65"
YPbPr:	43", 49", 55", 65"

Environmental Parameters

Operating Temperature:	0°C~50°C
Operating Humidity:	5-95% noncondens.

Mechanical Parameters

Dimensions W x H x D:	
43":	39"(996mm), 23.5"(596mm), 4.2"(107mm)
49":	44"(1110mm), 26"(660mm), 3.9"(100mm)
55":	50"(1269mm), 29.5"(749mm), 5.4"(137mm)
65":	50"(1533mm), 29.5"(900mm), 5.4"(144mm)
Weight 43":	54 lb (24Kg)
Weight 49":	72 lb (32Kg)
Weight 55":	78 lb (35Kg)
Weight 65":	124 lb (55Kg)

Regulatory Compliance: CE, FCC, ROHS

Manufactured to: ISO9001:2000

