

DNA1290M4

4M 32x Optical Zoom

D/N IP Zoom Box Camera

Analytics



DESCRIPTION

The DNA1290M4 Series are 1/2.8" CMOS 4MP Network IP Day Night Zoom Box Camera 32X Optical, 16x Digital Zoom are Network ready, that represent state-of-the-art, DSP based camera technology. Units are designed with H.265/H.264/MJG video compression and configurable triple stream outputs at 25/30fps 4MP (2560x1440). 1.3MP, 720p, D1 and CIF resolutions are available for outstanding quality images under Starlight low illumination – Color 0.005/F1.4/0.0005/BW/F1.4. Features are: block cameras and zoom lens receiver drivers, Auto Tracking, built-in intelligent analytics (IVS), EIS, Defog, OSD with D/N, BLC, HLC, WB, AGC, 3DNR, RJ-45 Ethernet port, Audio in/out, RS-485, 2 Alarms in/1 out, Smart Phone Interface, ONVIF and IP66. With input 12VDC/POE, the DNA1290M4 series IP D/N Zoom Box Camera with Analytics are designed to meet demanding, commercial and industrial Network Video surveillance installations.

FEATURES

- * Network 4MP D/N Integrated Zoom Box Cameras
- * 1/2.8" Starlight Progressive Scan Image Sensor
- * Illumination Starlight Color 0.005Lux/0.0005/BW
- * H.265/H.264/MJPEG and Triple Stream Encoder
- * 4MP with 32x Optical, 16x Digital Zoom
- * Day/Night ICR, WDR(120dB), Auto Iris and Focus
- * OSD with AWB, AGC, BLC, 3DNR, 2DNR
- * Up to 24 Zones Privacy Masking
- * Built-in Analytics: Tripwire, Perimeter protection, Loitering, abandoned objects, missing objects, Face Detection, Vehicle Capture, Camera tamper
- * Supports filtering false alarms: animals, leaves
- * Supports RTP/RTSP Unicast/Multicast
- * Variable Bit Rate and Constant Bit Rate
- * Audio in/out, 2 Alarms in 1 Relay out; RS-485
- * 10/100 Mbps Ethernet Compatible; RJ-45 Port
- * Smart Phone - iPhone, iPad and Android
- * Micro SD Card Slot local recording; 512GB
- * Available 12VDC Input Voltage, POE (802.3af)
- * Compliance with CE, FCC, ROHS, ONVIF

ORDERING INFORMATION

DNA1290M43A-4 4MP Integrated Zoom Box Camera 32X, NTSC, Audio, Data, Alarms, 12VDC/POE

DNA1290M43B-4 4MP Integrated Zoom Box Camera 32X, PAL, Audio, Data, Alarms, 12VDC/POE

DNA1290M43-IRH-4 Housing with IR LEDs for 100m Night Vision



APPLICATIONS

- * Homeland Security
- * Correctional Centers
- * Petrochemical Industry
- * Corporate and Banking
- * Casinos and Hospitality
- * Health Care Centers
- * Schools and Universities
- * Government and Military
- * Power Generating Plants
- * Traffic Surveillance (ITS)



DNA1290M4

4M 32x Optical Zoom

D/N IP Zoom Box Camera

Analytics



Video Specifications

Video Compression: H.265/ H.264 / MJPEG
 Frame Rate 2MP Main 4MP/720p; Sub D1/CIF

Max power consumption: 1.5A, 6W
 MTBF: 50,000 hours
 IR LED Housing: 100m Night Vision

Audio Specifications

Audio Compression: G711a/u(32kbps), PCM(128kbps)
 Interface: Terminal Block in/out

Network Parameters

Max User Access: 20 simultaneously
 Smart Phone: iPhone, Android

Data Specifications

RS-232: PC Control
 RS-422/RS-485: Terminal Block in/out
 Protocols/Baud Rate: Pelco D, 2400
 10/100Mbps Ethernet: RJ-45 Port

Mechanical Parameters

Net weight: 2.245lbs(1Kg)
 Dimensions LxWxH: 6.3"(160mm), 2.75"(70mm), 2.75"(70mm)

Auxiliary Specifications

Alarms: 2ch in/1 out Terminal Block
 Memory Card Slot: SD Micro - max. 512GB

Environmental Parameters

Operating temperature: -40°F~140°F (-40°C~60°C)
 Operating humidity: 0~90% non-condensing
Regulatory Compliance: CE, FCC, ROHS, ONVIF

Electrical Parameters

Input power: 12VDC, 50/60Hz; POE(802.3af)

Manufactured to: ISO9001 Standards

| Camera Parameters | DNA1290M43 |
|---------------------------|--|
| Image Sensor | Progressive Scan Exmor CMOS |
| Effective Pixels | 4.0M (2560x1440) |
| Output Pixels: | 2560(H)x1440(V) |
| Resolution (H) Pixels: | 4MP/ 1080p/720P / D1(704x576,704x480), CIF |
| Min. Illum. F1.6, 50 IRE: | Color 0.005Lux/0.0005 Lux/B/W |
| Frame Rate: | 4MP/2MP/720P(1~30fps); D1(1~30fps) |
| Optical / Digital Zoom: | 32X (4.8mm ~ 154mm) / 16X |
| View Angle: Wide x Tele | 55.8°(Wide) ~ 2.7°(Tele) |
| F-value: | F1.5 (wide) – F4.0 (telephoto) |
| Focus: | Auto/Manual (Far/Near) |
| IR Cut Filter Removable: | Auto(ICR) / Color / B/W |
| Electronic Shutter: | 1/1~1/10,000s |
| Wide Dynamic Range: | WDR (120dB) |
| Privacy Masking: | ON/OFF (up to 24 areas) |
| Electronic Shutter: | 1/1 to 1/10,000 s, Total 22 steps |
| IRIS: | Auto |
| BLC: | BLC / HLC / WDR (120dB) |
| White Balance: | Auto/ATW/Indoor/Outdoor/Manual |
| | |
| Encoder/Parameters | DNA1290M43 |
| Video Compression: | H.265/H.264/MJPEG, Triple Stream, Configurable |
| LAN Interface: | 10/100 Mbps RJ-45 Port |
| Output Bit Rate: | Variable Bit Rate (VBR) & Constant Bit Rate (CBR) |
| Network Interface: | 10/100 Mbps RJ-45 Port; Status and Network LEDs |
| Wireless Network: | IEEE 802.11a/b/d/e/g/h/i, 802.11n |
| Network Protocol: | IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour |
| Web Server: | Intuitive Browser Interface, Internet Explorer |
| Operating System: | Compatible with NVR Management and DNA2000, DNA3750, DNA3800, DNA4000, DNA5000 Series NVR Server Appliances |
| CPU Requirement: | Intel Core 4 Quad 2GHz or higher for Client |

