

DNA1345FWE

2MP IP D/N IR Eyeball Dome

H.265/H.264 Triple Stream

Analytics



DESCRIPTION

The DNA1345FWE Series are 1/2.8" Starvis CMOS, 2MP Network IP D/N IR Eyeball Domes. Vandal resistant units are designed with high quality Encoder H.265/H.264 video compression and configurable triple stream outputs at 50/60fps 2MP (1920x1080), 25/30fps at 720p. D1 and CIF Resolution are available providing outstanding quality images under Starlight ultra-low illumination - Color 0.009/F2.0/0Lux/IR LED on - 50m night vision. Features include ICR, 3DNR, AGC, BLC, true WDR (120dB), SD card and built-in analytics. Configured with 3.6mm, 2.8mm or 6mm fixed lenses, easy to install 3-axis 360° adjustable pan/tilt, Smart Phone Interface, ONVIF, impact protection IK10 and IP67. With 12VDC/POE, the DNA1345FWE Series 2MP Day/Night Network IR Eyeball Domes with Analytics are ideal solutions for demanding commercial, industrial IP video surveillance installations.

FEATURES

- * Network, 2.0 Megapixel, 1920x1080, Day/Night IR Eyeball Domes
- * 1/2.8" Starvis CMOS Scan Sensor; 120dB WDR
- * Illumination Starlight Color 0.009Lux/0Lux/IR on
- * H.265/H.264 Triple Stream configurable
- * Highest Rated Video Compression and DSP
- * Supports 50/60fps @ 2MP, 25/30fps at 720p
- * Built-in Analytics: Tripwire, Perimeter Protection, Loitering, Abandoned Objects, Missing Objects Face Detection, Scene Change, Camera Tamper
- * Easy to adjust 3 Axis Gimbal 360° Pan/Tilt
- * 3.6mm; optional 2.8mm, 6mm Fixed Lenses
- * Available with 16x Digital Zoom feature
- * Built-in IR LEDs for Night Vision - 50 meters
- * Variable Bit Rate and Constant Bit Rate
- * Supports RTP/RTSP Unicast/Multicast
- * 1ch Audio Input as built-in Microphone
- * 10/100Mbps Ethernet Compatible RJ-45 Port
- * Smart Phone interface: iPhone and Android
- * Vandal Impact Protection Rating IK10
- * Available with Voltage 12VDC and POE
- * Ethernet, Surge Protection; SD Card (128GB)
- * Compliance with CE, FCC, ROHS, ONVIF, IP67

ORDERING INFORMATION

- DNA1345FW-54E Network 2MP, D/N IR Eyeball Dome, 2.8mm 50m, IP67, 12VDC/POE
- DNA1345FW-64E Network 2MP, D/N IR Eyeball Dome, 3.6mm 50m, IP67, 12VDC/POE
- DNA1345FW-7A4E Network 2MP, D/N IR Eyeball Dome, 6mm 50m, IP67, 12VDC/POE



APPLICATIONS

- * Homeland Security
- * Correctional Centers
- * Petrochemical Industry
- * Corporate and Banking
- * Casinos and Hospitality
- * Health Care Centers
- * Schools and Universities
- * Government and Military
- * Power Generating Plants
- * Traffic Surveillance (ITS)



DNA1345FWE

2MP IP D/N IR Eyeball Dome

H.265/H.264 Triple Stream Analytics



DNA1345FWE	Product Specifications
Image Sensor:	2MP 1/2.8" Starvis CMOS Progressive Scan Image Sensor with WDR
Effective Pixels:	1920(H)×1080(V)
Minimum Illumination:	Color 0.009LUX/F2.0/BW, 0Lux(IR ON)
S/N Ratio:	> 50 dB
Ultra Dynamic Range:	True WDR 120dB
Auto Iris Control:	DC only
Lens /IR Night Vision:	2.8mm, 3.6mm, 6mm Fixed Focal Auto Iris / 50 meters IR LED ON
Digital Signal Processing:	High Quality Encoder with Reset Function
Video Compression:	H.265/H.264, Triple Stream, Configurable
Video Resolution:	2MP (1920 x 1080), 720p, D1, CIF
Video Frame Rate:	25/30fps @ 2MP, 720p
Audio Function:	Audio Input as built-in microphone
Audio Rate/ Compress.:	64kbps/128kbps; G.711 / PCM
Features:	ICR, 3DNR, AGC, BLC, AWB, true WDR (120dB)
Network Interface:	10/100 Mbps RJ-45 Port
Network Protocol:	HTTP, TCP/IP, ARP, IGMP, ICMP,RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, SNMP
Smart Phone/Appliance:	iPhone, iPad and Android
Web Server:	Intuitive Browser Interface
Built-in Analytics:	Tripwire - Motion Detection with alarm recording, Cross Warning Zone, Perimeter protection, loitering, abandoned objects, missing objects detection, face detection, scene detection, tamper detection, camera tamper warning message
CPU Requirement/OS:	Intel Core i7 2.4GHz/Linux with DNA3700, DNA3750, DNA3800, DNA4000, DNA5000 NVR
Micro SD Card Slot:	Supports Local Recording - max 128GB
Power Supply:	12VDC - 5W (IR ON); Power over Ethernet(>100m)
Operating Temperature:	14°F ~ 140°F (-10°C ~ 60°C)
Operating Humidity:	0-95% non-condensing
Dimensions Dia. x H:	4.17" (106mm) x 3.69" (94mm)
Weight:	1.04 lbs. (0.5Kg)
Materials:	Metal, rated IK10
Regulatory Compliance:	CE, FCC, ROHS, ONVIF, IP67
Manufactured to:	ISO9001:2000 Standards

