

# DNV1385W-24E

## 5MP IP D/N IR Eyeball Dome

### H.265/H.264 Dual Stream



#### DESCRIPTION

The DNV1385W-24E Series are 1/3" CMOS 5MP Network IP D/N IR Eyeball Domes. Units are designed with high quality Encoder H.265/H.264 video compression and configurable dual stream outputs, 25/30fps @5MP (2592x1920) resolution providing outstanding quality images under low illumination - 0Lux/IR LED on; 4 high output LEDs for 30m night vision. Features include ICR, 3DNR, AGC, BLC, true WDR (120dB), Audio in/out, Alarm in/out and SD card slot (128GB). Configured with vari-focal 2.7-13.5mm lens, easy-to-install, 3-axis gimbal, 360° adjustable pan/tilt, Smart Phone Interface (on NVR), ONVIF and IP66. With 12VDC/POE input, the DNV1385W-24E Series 5MP Day/Night Network IR Eyeball Domes are solutions for demanding commercial, industrial video surveillance installations.

#### FEATURES

- \* Network 5MP 2592x1920, Day/Night IR Eyeball Domes, true WDR (120dB)
- \* 1/3" CMOS Progressive Scan Sensor
- \* Minimum Illumination 0Lux/IR LED on
- \* H.265/H.264 Dual Stream Configurable
- \* Highest Rated Video Compression and DSP
- \* Supports 25/30fps @5MP, 4MP and 3MP
- \* Easy to adjust 3 Axis Gimbal 360° P/T
- \* Varifocal HD IR Lens 2.7-13.5mm
- \* Built-in 4 H/O IR LEDs for 30m Night Vision
- \* OSD with D/N, BLC, 3DNR, AWB, AGC, WDR, Picture Adjust Bright, Contrast, Sharpness
- \* 1 Audio In/1 Out; 1 Alarm In/1 Out
- \* 10/100Mbps Ethernet Compatible RJ-45 Port
- \* Smart Phone Interface: iPhone and Android
- \* Available with Voltage 12VDC and POE
- \* Ethernet, Surge Protection; SD Card (128GB)
- \* Compliance with CE, FCC, ROHS, IP66

#### ORDERING INFORMATION

DNV1385W-24E 5MP, D/N IR Eyeball Dome, 2.7-13.5mm, 30m, Audio, Alarms, 12VDC/POE



#### APPLICATIONS

- \* Homeland Security
- \* Correctional Centers
- \* Petrochemical Industry
- \* Corporate and Banking
- \* Casinos and Hospitality
- \* Health Care Centers
- \* Schools and Universities
- \* Government and Military
- \* Power Generating Plants
- \* Traffic Surveillance (ITS)



[www.dantesecurity.net](http://www.dantesecurity.net)

USA

[sales@dantesecurity.net](mailto:sales@dantesecurity.net)

# DNV1385W-24E

## 5MP IP D/N IR Eyeball Dome

### H.265/H.264 Dual Stream



DNV1385W-24E	Product Specifications
Image Sensor:	1/3" 5MP CMOS Progressive Scan Image Sensor WDR
Effective Pixels:	2592(H)×1920(V)
Minimum Illumination:	0Lux with IR LEDs ON
S/N Ratio:	> 52 dB
Dynamic Range:	True WDR 120dB
Auto Iris Control:	DC only
Lens /IR Night Vision:	2.7 ~ 13.5mm Vari-Focal
IR Distance:	30m with 4 high output LEDs
Video Resolution:	5MP
Video Frame Rate:	25/30 fps @ 5MP, 4MP, 3MP
Video Compatibility:	NTSC and PAL
OSD:	Multi-Language
Day/Night:	Auto(ICR) / Color / B/W / EXT
White Balance /BLC:	ATW / Auto
Auto Gain Control:	ON
Noise Reduction:	3DNR
Picture Adjustment:	Mirror / Brightness / Contrast / Sharpness / Hue / Gain
Defog:	no IR Diffusion
Power Supply:	12VDC - 600mA (IR ON) and POE
Operating Temperature:	-22°F ~ 140°F (-30°C ~ 60°C)
Operating Humidity:	0-95% non-condensing
Dimensions Dia. x H:	4.72" (120mm) X 4.2" (107mm)
Weight:	1.7 lbs. (860g)
Materials:	Aluminum; Waterproof
Regulatory Compliance:	CE, FCC, ROHS, IP66
Manufactured to:	ISO9001:2000 Standards

