

# DZ6818-5500 Series 18" Explosion Proof Housing w/IR LEDs



## DESCRIPTION

The DZ6818-5500 Series are IP68 rated, Stainless Steel 316L, Explosion Proof rugged grade, corrosion resistant housings for fixed box or zoom style cameras, analog HD or IP. Units provide built-in IR LEDs for up to 100m night vision. Features include blower, heater, and optional sunshield. The housings are designed with 24VAC input voltage, available 12VDC for heater/blower modules and camera feeds. With optional 85-265VAC the Series DZ6817-5500 Explosion Proof IR Housings meet the most demanding commercial, industrial and marine environment, video surveillance installations.



Bracket

## FEATURES

- \* Explosion Proof Housings w/ IR Illuminators
- \* IR LEDs with up to 100m Night Vision
- \* Support of LED light controls
- \* Stainless Steel 316L, Tempered Glass
- \* Blower, Heater, optional Sunshield
- \* Two (2) Cable Entry Glands
- \* 24VAC, 85-265VAC input voltages
- \* Certified for Exd II CT6/DIP A20 TA, T6
- \* Regulatory Compliance with IP68

## APPLICATIONS

- \* Homeland Security
- \* Correctional Centers
- \* Petrochemical Industry
- \* Marine Environment
- \* Government and Military
- \* Power Generating Plants

## ORDERING INFORMATION

DZ6818-5503	Explosion Proof, SS316L, IP68 rated, 18"L Housing, LEDs 100m, 24VAC
DZ6818-5505	Explosion Proof, SS316L, IP68 rated, 18"L Housing, LEDs 100m, 85-265VAC
DZ6700-55A	Wall Mount Steel Bracket with swivel



# DZ6818-5500 Series 18" Explosion Proof Housing w/IR LEDs



## Electrical Parameters:

Input Voltage: 24VAC, 85-265VAC  
 Camera Power: 12VDC provided in Heater  
 Blower Module  
 Consumption: 25W with Camera  
 Heater/Blower: Included

Material: Stainless Steel 316L Grade  
 Sunshield: optional  
 Glass: 2.95" (75mm) dia. x 10mm thick  
 Material: Tempered Grade  
 Weight: 20.2 lb. (9Kg) (no sunshield)  
 Cable Glands Thread: 2pcs G3/4 or NPT3/4

## IR Arrays

Wavelength: 850nm  
 Distance: Up to 100m  
 View Angle: 30° ~ 60°

## Environmental Parameters

Operating Temperature: -13°F~140°F(-25°C~60°C)  
 Storage Temperature: -13°F~158°F (-25°C~70°C)  
 Humidity: 0~95% (Non-condensing)

## Mechanical Parameters

Outside Dimension: 17.6" (447mm) L  
 6.54" (166mm) W  
 6.73" (171mm) H  
 Inside Dimension: 6.7" (170mm) L  
 Camera-lens available  
 space; with heater, blower  
 3.15" (80mm) dia.  
 3.15" (80mm) H

## Regulatory Compliance

Rating: IP68  
 Certified: Exd II CT6/DIP A20 TA, T6

**Manufactured to:** IS09001:2000  
 Standards

**Option**  
 Bracket with Swivel: DZ6700-55A

